

using a die element having an upper striking edge;
applying impact force over substantially all of the upper striking edge
simultaneously with each impact from the striking tool; and
applying the impact force from a striking tool having a contact surface with
a lateral dimension which is greater than a largest transverse dimension between
opposite sides of the upper striking edge.

20. A method as defined in claim 17 further comprising the step of:

applying impact force over substantially all of the upper striking edge with
each impact from the striking tool, the contact surface of the striking tool having a
lateral dimension which is greater than the majority of the largest transverse dimension
between opposite sides of the striking edge.

21. A method as defined in claim 17 further comprising the step of:

scraping a layer of material from an inner surface of the shell to reduce
the thickness of the shell to an amount less than a height dimension between the
cutting and striking edges of the die element.

22. A method as defined in claim 21 further comprising the step of:

using a scoop and scraping tool to scrape the layer of material from the
shell.

23. **(Amended)** A method of carving shapes in the shell of a pumpkin, fruit or
vegetable which comprises driving a cutting die element through the shell by striking the
die element with a striking tool, and further comprises steps of:

using a die element having a lower cutting edge and an upper striking
edge;

applying impact force over substantially all of the upper striking edge
simultaneously with each ~~impact from~~ strike of the striking tool against the die
element; and

using a striking tool having an integral contact surface with a lateral
dimension which is greater than a largest transverse dimension between opposite sides
of the upper striking edge to apply the impact force; and

striking the striking tool against the die element to create each impact by moving the contact surface of the striking tool from a position spaced from the die element into contact with the striking edge.

24. A method as defined in claim 23 further comprising the step of:
driving the die element into the pumpkin shell until the cutting edge passes through an inner surface of the pumpkin shell.

25. A method as defined in claim 23 further comprising the step of:
removing a cut-out section of the shell which is surrounded by the die element after the die element is driven into the shell;
pushing the cut-out section into the interior of the pumpkin while the die element remains in the shell; and,
removing the die element from the pumpkin shell after the cut-out section has been removed from the die element.

26. (Amended) A method ~~as defined in claim 23~~ of carving shapes in the shell of a pumpkin, fruit or vegetable which comprises driving a cutting die element through the shell by striking the die element with a striking tool, and further comprising the step of:

using a die element having a lower cutting edge and an upper striking edge;

applying impact force over substantially all of the upper striking edge simultaneously with each impact from the striking tool;

using a striking tool having a contact surface with a lateral dimension which is greater than a largest transverse dimension between opposite sides of the upper striking edge to apply the impact force; and

scraping a layer of material from the shell at an inner surface of the shell to reduce the thickness of the shell to an amount less than a dimension between the cutting and striking edges of the die element.

27. (Amended) A method ~~as defined in claim 23~~ further comprising the step of:

using of carving shapes in the shell of a pumpkin, fruit or vegetable
which comprises driving a cutting die element having a through the shell by striking
the die element with a striking tool, and further comprises steps of:

using a die element having a lower serrated cutting edge and an upper
striking edge;

applying impact force over substantially all of the upper striking
edge simultaneously with each impact from the striking tool;

using a striking tool having a contact surface with a lateral
dimension which is greater than a largest transverse dimension between
opposite sides of the upper striking edge to apply the impact force; and

forcing a portion of the serrated cutting edge into an outer surface of the
shell to hold the die element in position on the shell before striking the die element with
the striking tool.

28. A method of carving shapes in the shell of a pumpkin, fruit or vegetable
which comprises the steps of:

using a die element having a lower serrated cutting edge and an upper
striking edge;

scraping a layer of material from the shell at an inner surface of the shell
to reduce the thickness of the shell to an amount less than a dimension between the
cutting and striking edges of the die element;

piercing the outer surface of the shell with the serrated cutting edge to
hold the die element in position on the shell; and

forcing the die element into the shell until the cutting edge passes through
an inner surface of the shell.

29. A method as defined in claim 28 further comprising the step of:

using a scoop and scraping tool to scrape the layer of material from the
shell; and

removing a cut-out section of the shell which is surrounded by the die
element after the die element is forced into the shell.

30. (New) A method as defined in claim 23 further comprising the steps of:
using a cutting die element having a serrated cutting edge; and
forcing a portion of the serrated cutting edge into an outer surface of the shell with finger pressure to hold the die element in position on the shell before striking the die element with the striking tool.

31. (New) A method as defined in claim 30 further comprising the steps of:
using a die element with tips on the serrated cutting edge; and
piercing the outer surface of the pumpkin shell with at least two of the tips of the serrated cutting edge to hold the die element in position prior to striking the die element with the striking tool.

32. (New) A method as defined in claim 24 further comprising the step of:
scraping a layer of material from an inner surface of the shell to reduce the thickness of the shell to an amount less than a height dimension between the cutting and striking edges of the die element.

33. (New) A method as defined in claim 26 further comprising the steps of:
using a cutting die element having a serrated cutting edge; and
forcing a portion of the serrated cutting edge into an outer surface of the shell with finger pressure to hold the die element in position on the shell before striking the die element with the striking tool.

34. (New) A method as defined in claim 26 further comprising the steps of:
using a die element with tips on the cutting edge; and
piercing the outer surface of the pumpkin shell with at least two of the tips of the cutting edge to hold the die element in position prior to striking the die element with the striking tool.

35. (New) A method as defined in claim 26 further comprising the step of:

driving the die element into the pumpkin shell until the cutting edge passes through an inner surface of the pumpkin shell.

36. (New) A method as defined in claim 26 further comprising the step of:

removing a cut-out section of the shell which is surrounded by the die element after the die element is driven into the shell.

37. (New) A method as defined in claim 36 further comprising the step of:

removing the die element from the pumpkin shell after the cut-out section has been removed from the die element.

38. (New) A method as defined in claim 26 further comprising the step of:

using a scoop to scrape the layer of material from the shell.

39. (New) A method as defined in claim 27 further comprising the steps of:

using a die element with tips on the serrated cutting edge; and
piercing the outer surface of the pumpkin shell with at least two of the tips of the serrated cutting edge to hold the die element in position prior to striking the die element with the striking tool.

40. (New) A method as defined in claim 27 further comprising the steps of:

scraping a layer of material from an inner surface of the shell to reduce the thickness of the shell to an amount less than a height dimension between the cutting and striking edges of the die element.

41. (New) A method as defined in claim 40 further comprising the step of:

using a scoop and scraping tool to scrape the layer of material from the shell.

42. (New) A method as defined in claim 40 further comprising the step of:

driving the die element into the pumpkin shell until the cutting edge passes through an inner surface of the pumpkin shell.

43. (New) A method as defined in claim 42 further comprising the step of:

removing a cut-out section of the shell which is surrounded by the die element after the die element is driven into the shell.

44. (New) A method as defined in claim 43 further comprising the step of:

removing the die element from the pumpkin shell after the cut-out section has been removed from the die element.

45. (New) A method as defined in claim 28 further comprising the step of:

removing a cut-out section of the shell which is surrounded by the die element after the die element is driven into the shell.

46. (New) A method as defined in claim 45 further comprising the step of:

removing the die element from the pumpkin shell after the cut-out section has been removed from the die element.